Supply of RTD Sensor (100nos)

Reference Order No.: iSenS/MLP2030/2023-24/GEM_13

- 1. The order should not be preferably split. The comprehensive quote considering fabrication/fitment of all components, for at CSIO will be considered.
- 2. The required quantity is mentioned against each component in annexure 1. The components should be sealed /packed as per the original factory packing. If found damaged, will be returned.
- 3. The price should be including ex-CSIO delivery.
- 4. The valid coc/inspection report should be shared wherever applicable.
- 5. The supplier should share the authorization letter from the OEM, wherever applicable.
- 5. Payment and other things as per CSIO norms.
- 6. Pl mail at spo@csio.res.in and kumarmukesh@csio.res.in
- 7. Quote time by 11:00AM on 11.03.2024.
- 8. The details of the user will not be shared.
- 9. Material to be supplied on or before March 15, 2024

Specifications

Sheath Material: SS304Sheath OD (in mm): 3Sensor Type: PT100

Sensor Type: PT100
RTD Element (Wire) Material: Platinum

• Configurations: Simplex

• Junction Wire (wire configuration):3-Wire

Head Enclosure type: SS304Extension Cable Length: 1 Meter

• Temperature Range:-250 to 100 degree Celsius

• Nominal Length of RTD: 150 mm

• Immersion Length: 30 mm