SUPPLY OF Industrial Cellular Router with SIM Slot

Reference Order No.: ISenS/HCP-53/2023-24/DP-01

- 1. THE ORDER SHOULD NOT BE PREFERABLY SPLIT. THE COMPREHENSIVE QUOTE CONSIDERING FABRICATION/FITMENT OF ALL COMPONENTS, FOR AT CSIO WILL BE CONSIDERED.
- 2. THE REQUIRED QUANTITY IS MENTIONED AGAINST EACH COMPONENT IN ANNEXURE 1. THE COMPONENTS SHOULD BE SEALED /PACKED AS PER THE ORIGINAL FACTORY PACKING. IF FOUND DAMAGED, WILL BE RETURNED.
- 3. THE PRICE SHOULD BE INCLUDING EX-CSIO DELIVERY.
- 4. THE VALID COC/INSPECTION REPORT SHOULD BE SHARED WHEREVER APPLICABLE.
- 5. THE SUPPLIER SHOULD SHARE THE AUTHORIZATION LETTER FROM THE OEM, WHEREVER APPLICABLE
- 5. PAYMENT AND OTHER THINGS AS PER CSIO NORMS
- 6. PL MAIL AT spo@csio.res.in and akbansal@csio.res.in
- 7. QUOTE TIME 7 DAYS FROM THE DATE OF TENDER.
- 8. THE DETAILS OF THE USER WILL NOT BE SHARED.
- 9. SUPPLIER TO SHARE THE DELIVERY TIMELINES AFTER PO AND PAYMENT TERMS. RELEASE OF PO IS PURELY THE PREROGATIVE OF CSIO.

Industrial Cellular Router with SIM Slot

Specifications

- 1. Rugged Industrial type
- 2. Mobile Module 4G/LTE
- 3. LAN 10/100 Mbps Ethernet RJ45 ports (minimum 2 ports)
- 4. Cellular connectivity
- 5. Antenna for LTE
- 6. SIM slot (which can fit all types of SIM)
- 7. LEDs for Power, connection status and signal strength
- 8. Open VPN, IPsec, GRE Tunnel
- 9. Automatic periodic reboot
- 10. System log to record the status of the router
- 11. Remote management
- 12. Over the air firmware update
- 13. Network Address Translation
- 14. Port Forwarding
- 15. Inbound and outbound port filtering
- 16. Inbound and outbound Trusted IP
- 17. Input voltage Range 9-30V DC
- 18. Power consumption ≤6.5W
- 19. Reverse polarity protection
- 20. Operating temperature -40°C to +75°C
- 21. Humidity 10% to 90% non-condensing
- 22. CE RoHS compliant
- 23. Factory reset button

Also attach the product brochure/catalogue of the router to be supplied as part of this tender.